

ISCAN*

Your Safety, Our Priority

4K ULTRAHD IP CAMERA 8 ล้านพิกเซล

กล้องวงจรปิดความละเอียดสูงแบบโดม (Dome Camera). รุ่น IS-D5680IR-IP ถูกออกแบบให้ เกาะกักรัด สวยงาม ด้วยรูปทรงโดมแบบครึ่งวงกลม เหมาะสำหรับการติดตั้งใช้งานในพื้นที่ภายในอาคาร ในสำนักงาน ห้องประชุม ที่ต้องการความละเอียดสูง เมื่อติดตั้งแล้วจะดูกลมกลืนไปกับห้อง ไม่สะดุดตา

คุณสมบัติโดยทั่วไป

ฐานกล้องทำจากโลหะ เพื่อความคงทนและการระบายความร้อนที่ดียิ่งขึ้น IP66 ป้องกันได้ทั้งฝุ่นและคราบฝนตกอย่างหนักได้ ความละเอียดสูง 4 ล้านพิกเซล และความคมชัดระดับ 4K มีหลอดอินฟราเรด เพื่อช่วยบันทึกภาพในช่วงเวลากลางคืน รองรับระบบตรวจจับใบหน้า และ ระบบตรวจจับคน รองรับการดูภาพผ่านมือถือทั้งระบบ iOS และ ANDRIOD

ข้อมูลทางเทคนิค

- 1/2.7" Low ILLUMINATION CMOS SENSOR,0.0001LUX@F1.2,BLACK/WHITE 0.0001LUX@F1.2
- H.265/H.264, SUPPORT DUAL STREAM, AVI;0.1M~8MPBS VARIABLE; 1~30F/S VARIABLE
- IMAGE OUTPUT MAIN STREAM: 8MP 3840*2160@15FPS, 5MP 2880*1616@25FPS, 4MP 560*1440@25FPS, 2MP 1920*1080@25FPS. SUB-STREAM: 800*448@25FPS;
- SHUTTER 1/50(1/60)s TO 1/10,000s
- BOARD LENS 3.6MM , IR LEDS 15PCS Φ 5 IR LEDS ,IR DISTANCE UP TO 10M
- AUDIO G.711, BUILT IN MICROPHONE (OPTIONAL)
- DAY AND NIGHT BUILT-IN IR-CUT, DAY/NIGHT AUTO SWITCH
- NOISE REDUCTION SUPPORT 2D/3D , WIDE DYNAMIC SUPPORT DIGITAL
- NETWORK INTERFACE 1*RJ45 10/100M ADAPTIVE ETHERNET PORT; SUPPORT RTSP/FTP/DHCP/NTP/UPNP ,ETC
- SUPPORTING FACE DETECTION, HUMANOID DETECTION ,ONVIF SUPPORT
- SUPPORT MULTIPLE MOBILE MONITORING (IOS, ANDROID)
- PoE SUPPORT , DC12V/2A INPUT, POWER CONSUMPTION: \leq 3W
- MATERIAL ALUMINUM , DIMENSION 102MM(Φ)X80MM(H) ,WEIGHT APPROX.350G



ติดต่อเรา

02-9393151-8 (ออฟฟิศ)

090-6576986 (เซลส์เน็ต)

065-5397939 (เซลส์วัน)



IS-D5680IR-IP

ANA DIGIT GROUP CO.,LTD
1408/9-10 Paholyothin Rd., Jomphol
Jatujak Bangkok Thailand 10900

